

Tender specification KLAUS Multiparking TrendVario 6200+

Preliminary technical remarks

1. Basis for the design are:
 - 1.1 the garage regulations (GaVo) according to the building regulations in the latest version,
 - 1.2 the EC Machinery Directive 2006/42/EC, Appendix 1, and the DIN EN 14010
 - 1.3 a voluntary conformity testing by TÜV SÜD
 - 1.4 the architect's workshop drawings
 2. The bidder confirms upon submission of the bid that the garage dimensions and the driveway widths comply with the GaVo, the relevant implementation guidelines to be specified by him and the system offered by him.
 3. Required surface loads according to DIN 1991-1-1, per parking space: 2.0 t
-

Specification

General:

Multiparking system for independent parking of vehicles above and next to each other.

The system can be driven through and combined with the TrendVario 6100, 6100+, 6200+, 6300 and 6300+ systems (for details of these systems, please refer to the corresponding product data sheets).

Dimensions according to the underlying building, width and height dimensions.

The parking spaces must be accessed horizontally (installation tolerance $\pm 1\%$).

There must be a driveway across the entire width of the system (observe the minimum width of the driveway in accordance with local regulations).

The parking spaces are arranged on 2 levels, one above the other. The vehicles park on stable steel platforms.

The platforms on the upper floor (UF) are moved vertically, the platforms on the first floor (GF) horizontally. There is always 1 parking space less on the entrance level (first floor). This empty space is used to move the first floor parking spaces sideways so that an upper floor parking space above can be lowered to the entrance level. This means that 3 parking spaces (1 on the first floor, 2 on the upper floor) are the smallest unit for this parking system.

Positioning of the vehicle in each parking space by means of a positioning aid attached to one side (to be set in accordance with the operating instructions).

For safety reasons, the platforms are always moved behind locked gates.

All necessary safety devices are installed. They essentially consist of a chain monitoring system, locking levers for the upper platforms and locked gates. The gates can only be opened when the selected parking space has reached its parking position.

Tender specification KLAUS Multiparking TrendVario 6200+

Sliding doors:

Size:

- Sliding door, dimensions: approx. 2500 mm x 2000 mm (width x height).

Frame:

- Frame construction with a vertical central bar made of extruded aluminum profiles (anodized, layer thickness approx. 20 µm)
- A recessed handle is integrated into a vertical aluminum profile to open the doors.
- A rubber lip is attached to the closing edge for a clean finish to the building.

Standard door panel

Perforated aluminum sheet

- Thickness 2 mm, RV 5-8 E6/EV1, anodized, layer thickness approx. 20 µm
- Ventilation cross-section of the infill approx. 40%

Door infill Alternative

Smooth aluminum sheet

- Thickness 2 mm, E6/EV1, anodized, layer thickness approx. 20 µm

Steel corrugated sheet

- Thickness 1 mm, galvanized, layer thickness approx. 20 µm
- Additionally powder-coated, layer thickness approx. 25 µm on the outside and approx. 12 µm on the inside
- Color options for the outside (building view): RAL 1015 (light ivory), RAL 3003 (ruby), RAL 5014 (pigeon blue), RAL 6005 (moss green), RAL 7016 (anthracite gray), RAL 7035 (light gray), RAL 7040 (window gray), RAL 8014 (sephia), RAL 9006 (white aluminum), RAL 9016 (traffic white)
- Inside of the doors in a light shade of gray

Timber infill

- Nordic spruce in A-grading
- Vertical tongue and groove boards
- colorless pre-impregnated

Laminated safety glass

- VSG made of ESG 8/4mm

wire mesh

- Mesh size 12 x 12 mm
- Wire diameter 2 mm, galvanized, layer thickness approx. 20 µm
- Ventilation cross-section of the infill approx. 70%

Running rails

- The running gear consists of 2 double-pair roller units per door, height-adjustable
- The running rails of the doors are attached with ceiling sleeves to brackets or directly to the concrete lintel or to a building-specific door suspension system
- The bottom guide consists of 2 plastic rollers on a base plate, which is dowelled to the floor
- Guide rails, ceiling sleeves and guide roller base plate are galvanized

Tender specification KLAUS Multiparking TrendVario 6200+

Gate operation

Electric drive by means of an electric motor, which is attached to the rail system at the turning point of the sliding gates. The drive pinion engages with a chain attached to the gate. For safety reasons, the platforms are always moved behind locked gates. Querying the positions "Door open" and "Door closed" positions are queried by electrical signal transmitters.

Separation (if required):

- On request

Please note: Door panels (side, track cover, etc.) and door suspensions are not included in the standard version, but can be supplied as optional extras at an extra charge.

Control system

- Central control point (control panel with emergency stop) for selecting the desired parking space
- The electrical wiring is carried out from the control cabinet by the supplier

Corrosion protection:

Corrosion protection in accordance with DIN EN ISO 12944-2, corrosivity class C3 moderate

- Platform profiles hot-dip galvanized in accordance with DIN EN ISO 1461, coating thickness min. 45 µm
- Side members hot-dip galvanized in accordance with DIN EN ISO 1461, coating thickness min. 55 µm
- Cross members hot-dip galvanized in accordance with DIN EN ISO 1461, coating thickness min. 55 µm
- Access plates hot-dip galvanized in accordance with DIN EN ISO 1461, coating thickness min. 55 µm
- Platform profile fastening screws stainless steel V4A
- Hydraulic pipes, fittings, bolts, screws, nuts, washers galvanized
- Other steel parts such as steel structure, bearing plates, drive brackets Hot-dip galvanized according to DIN EN ISO 1461 Coating thickness min. 55 µm.

Switch cabinet and main switch:

Access to the switch cabinet (approx. 60 x 60 x 25 cm) must be possible without danger. The lockable main switch must be positioned so that the entire entry area of the system can be seen.

Please consult KLAUS Multiparking if there is a wall opening from the control cabinet to the system.

Tender specification KLAUS Multiparking TrendVario 6200+

On-site services:

1. Electrical supply to the main switch / Foundation earth connector:
Suitable electrical supply to the main switch and the control wire line must be provided by the customer during installation. The functionality can be monitored on site by our fitters together with the electrician. If this cannot be done during installation for some reason for which the customer is responsible, the customer must commission an electrician at their own expense and risk.
In accordance with DIN EN 60204, grounding of the steel structure is necessary, provided by the customer (distance between grounding max. 10 m).
2. Safety fences:
Any constraints that may be necessary according to DIN EN ISO 13857 in order to provide protection for pathways directly in front, next to or behind the unit. This is also valid during construction.
3. Numbering of parking spaces:
Consecutive numbering of parking spaces.
4. Building services:
Any required lighting, ventilation, fire extinguishing and fire alarm systems as well as clarification and compliance with the relevant regulatory requirements.
5. Strip foundations:
If strip foundations are installed due to structural conditions, a walk-on platform must be erected on site at the height of the upper edge of the strip foundations in order to be able to carry out the installation work.
6. Drainage:
It is recommended that a water collection channel is provided in the center area of the pit and that this is with a floor inlet or a scoop pit (50 x 50 x 20 cm). A lateral slope is possible within the channel, but not in the rest of the pit area (longitudinal slope is given by the construction dimensions). In the interests of environmental protection, it is recommended that the pit floor be painted. Oil and petrol separators must be taken into account when connecting to the sewage system in accordance with legal regulations
7. Door suspensions:
The lintel height H2 (see product data sheet TrendVario 6200+) is necessary. With differing heights, additional fixings are required for extra charge
8. Door shields:
Door shields that may be necessary. If desired, they can be ordered from KLAUS Multiparking for an additional charge.
9. Wall cuttings:
Any necessary wall cuttings according to product data sheet TrendVario 6200+.
9. Concrete quality:
Floor and walls are to be made of concrete (quality minimum C20/25).

Tender specification KLAUS Multiparking TrendVario 6200+

Multiparking system for __ cars
TrendVario 6200+/160

Multiparking system for __ cars
GF: __ parking places + 1 empty space
UF: __ parking places

Clearance up to lower edge of the ceiling: 330 cm

Vehicle height:
GF: 150 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 335: car height UF 155 cm
Height 340: car height UF 160 cm
Height 345: car height UF 165 cm
Height 350: car height UF 170 cm
Height 355: car height UF 175 cm
Height 360: car height UF 180 cm
Height 365: car height UF 185 cm
Height 370: car height UF 190 cm
Height 375: car height UF 195 cm
Height 380: car height UF 200 cm
Height 385: car height UF 205 cm
Height 390: car height UF 210 cm
Height 395: car height UF 215 cm
Height 400: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Extra costs for remote control

Extra costs for additional hand-held transmitter (1 per parking place)

Extra costs for door panel made of plain aluminium sheet

Extra costs for door panel made of beaded steel plate

Extra costs for door panel made of wood

Extra costs for door panel made of laminated safety glass

Extra costs for door panel made of wire grating 12 x 12 mm

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/165

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 335 cm

Vehicle height:

GF: 155 cm

UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 340: car height UF 155 cm

Height 345: car height UF 160 cm

Height 350: car height UF 165 cm

Height 355: car height UF 170 cm

Height 360: car height UF 175 cm

Height 365: car height UF 180 cm

Height 370: car height UF 185 cm

Height 375: car height UF 190 cm

Height 380: car height UF 195 cm

Height 385: car height UF 200 cm

Height 390: car height UF 205 cm

Height 395: car height UF 210 cm

Height 400: car height UF 215 cm

Height 405: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation

incl. electrical wiring from hydraulic unit

incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/170

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 340 cm

Vehicle height:

GF: 160 cm

UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 345: car height UF 155 cm

Height 350: car height UF 160 cm

Height 355: car height UF 165 cm

Height 360: car height UF 170 cm

Height 365: car height UF 175 cm

Height 370: car height UF 180 cm

Height 375: car height UF 185 cm

Height 380: car height UF 190 cm

Height 385: car height UF 195 cm

Height 390: car height UF 200 cm

Height 395: car height UF 205 cm

Height 400: car height UF 210 cm

Height 405: car height UF 215 cm

Height 410: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation

incl. electrical wiring from hydraulic unit

incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/175

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 345 cm

Vehicle height:

GF: 165 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 350: car height UF 155 cm
Height 355: car height UF 160 cm
Height 360: car height UF 165 cm
Height 365: car height UF 170 cm
Height 370: car height UF 175 cm
Height 375: car height UF 180 cm
Height 380: car height UF 185 cm
Height 385: car height UF 190 cm
Height 390: car height UF 195 cm
Height 395: car height UF 200 cm
Height 400: car height UF 205 cm
Height 405: car height UF 210 cm
Height 410: car height UF 215 cm
Height 415: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/180

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 350 cm

Vehicle height:

GF: 170 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 355: car height UF 155 cm
Height 360: car height UF 160 cm
Height 365: car height UF 165 cm
Height 370: car height UF 170 cm
Height 375: car height UF 175 cm
Height 380: car height UF 180 cm
Height 385: car height UF 185 cm
Height 390: car height UF 190 cm
Height 395: car height UF 195 cm
Height 400: car height UF 200 cm
Height 405: car height UF 205 cm
Height 410: car height UF 210 cm
Height 415: car height UF 215 cm
Height 420: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/150

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 355 cm

Vehicle height:

GF: 175 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 360: car height UF 155 cm
Height 365: car height UF 160 cm
Height 370: car height UF 165 cm
Height 375: car height UF 170 cm
Height 380: car height UF 175 cm
Height 385: car height UF 180 cm
Height 390: car height UF 185 cm
Height 395: car height UF 190 cm
Height 400: car height UF 195 cm
Height 405: car height UF 200 cm
Height 410: car height UF 205 cm
Height 415: car height UF 210 cm
Height 420: car height UF 215 cm
Height 425: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/190

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 360 cm

Vehicle height:

GF: 180 cm

UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 365: car height UF 155 cm

Height 370: car height UF 160 cm

Height 375: car height UF 165 cm

Height 380: car height UF 170 cm

Height 385: car height UF 175 cm

Height 390: car height UF 180 cm

Height 395: car height UF 185 cm

Height 400: car height UF 190 cm

Height 405: car height UF 195 cm

Height 410: car height UF 200 cm

Height 415: car height UF 205 cm

Height 420: car height UF 210 cm

Height 425: car height UF 215 cm

Height 430: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation

incl. electrical wiring from hydraulic unit

incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/195

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 365 cm

Vehicle height:

GF: 185 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 370: car height UF 155 cm
Height 375: car height UF 160 cm
Height 380: car height UF 165 cm
Height 385: car height UF 170 cm
Height 390: car height UF 175 cm
Height 395: car height UF 180 cm
Height 400: car height UF 185 cm
Height 405: car height UF 190 cm
Height 410: car height UF 195 cm
Height 415: car height UF 200 cm
Height 420: car height UF 205 cm
Height 425: car height UF 210 cm
Height 430: car height UF 215 cm
Height 435: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/200

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 370 cm

Vehicle height:

GF: 190 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 375: car height UF 155 cm
Height 380: car height UF 160 cm
Height 385: car height UF 165 cm
Height 390: car height UF 170 cm
Height 395: car height UF 175 cm
Height 400: car height UF 180 cm
Height 405: car height UF 185 cm
Height 410: car height UF 190 cm
Height 415: car height UF 195 cm
Height 420: car height UF 200 cm
Height 425: car height UF 205 cm
Height 430: car height UF 210 cm
Height 435: car height UF 215 cm
Height 440: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/205

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 375 cm

Vehicle height:

GF: 195 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 380: car height UF 155 cm
Height 385: car height UF 160 cm
Height 390: car height UF 165 cm
Height 395: car height UF 170 cm
Height 400: car height UF 175 cm
Height 405: car height UF 180 cm
Height 410: car height UF 185 cm
Height 415: car height UF 190 cm
Height 420: car height UF 195 cm
Height 425: car height UF 200 cm
Height 430: car height UF 205 cm
Height 435: car height UF 210 cm
Height 440: car height UF 215 cm
Height 445: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/210

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 380 cm

Vehicle height:

GF: 200 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 385: car height UF 155 cm
Height 390: car height UF 160 cm
Height 395: car height UF 165 cm
Height 400: car height UF 170 cm
Height 405: car height UF 175 cm
Height 410: car height UF 180 cm
Height 415: car height UF 185 cm
Height 420: car height UF 190 cm
Height 425: car height UF 195 cm
Height 430: car height UF 200 cm
Height 435: car height UF 205 cm
Height 440: car height UF 210 cm
Height 445: car height UF 215 cm
Height 450: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/215

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 385 cm

Vehicle height:

GF: 205 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 390: car height UF 155 cm
Height 395: car height UF 160 cm
Height 400: car height UF 165 cm
Height 405: car height UF 170 cm
Height 410: car height UF 175 cm
Height 415: car height UF 180 cm
Height 420: car height UF 185 cm
Height 425: car height UF 190 cm
Height 430: car height UF 195 cm
Height 435: car height UF 200 cm
Height 440: car height UF 205 cm
Height 445: car height UF 210 cm
Height 450: car height UF 215 cm
Height 455: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Option:

Multiparking system for ___ cars
TrendVario 6200+/220

Multiparking system for ___ cars
GF: ___ parking places + 1 empty space
UF: ___ parking places

Clearance up to lower edge of the ceiling: 390 cm

Vehicle height:

GF: 210 cm
UF: 150 cm

If the clearance to the lower edge of the ceiling is deviant:

Height 395: car height UF 155 cm
Height 400: car height UF 160 cm
Height 405: car height UF 165 cm
Height 410: car height UF 170 cm
Height 415: car height UF 175 cm
Height 420: car height UF 180 cm
Height 425: car height UF 185 cm
Height 430: car height UF 190 cm
Height 435: car height UF 195 cm
Height 440: car height UF 200 cm
Height 445: car height UF 205 cm
Height 450: car height UF 210 cm
Height 455: car height UF 215 cm
Height 460: car height UF 220 cm

Vehicle length: 500 cm

Usable platform width: 230 cm

Platform load: 2,0 t

incl. freight, unloading, installation
incl. electrical wiring from hydraulic unit
incl. expert acceptance

Tender specification KLAUS Multiparking TrendVario 6200+

Optional position

Extra costs for larger platform width _____ cm

Optional position

Extra costs for increase of platform load to 2.6 t per parking space

Optional position

Extra costs for increase of platform load to 3.0 t per parking space

Optional position

Extra costs for parking place extensions for car length up to 5.10 m

Optional position

Extra costs for parking place extensions for car length up to 5.20 m

Optional position

Extra costs for parking place extensions for car length up to 5.30 m

Optional position

Platform coating in AluLongLife

Optional position

Platform coating in EasyWalk

Optional position

Extra costs for additional noise protection measures to protect against structure-borne sound according to DIN 4109-1

Optional position

Extra costs for additional increased noise protection measures to protect against structure-borne sound according to VDI 4100

Optional position

Extra costs for fixing in waterproof concrete with glue dowel

Extra costs for conclusion of a system service contract SSV "PLUS" with cleaning and care, incl. maintenance 2 per year, all spare and wear parts, and cleaning and care of the platform surface.
